## EUROPEAN PATENT COC

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

07293334

**PUBLICATION DATE** 

07-11-95

APPLICATION DATE

28-04-94

**APPLICATION NUMBER** 

06092275

APPLICANT:

SANYO ELECTRIC CO LTD;

INVENTOR:


KUROSAWA YOSHIAKI;

INT.CL.

F02G 1/057 B21F 45/00 F25B 9/00

TITLE

**EXTERNAL COMBUSTION ENGINE** 



ABSTRACT:

PURPOSE: To prevent deterioration of engine efficiency by preventing leakage of operation medium generated at a gap between a regenerator and a housing, and reducing thermal loss caused thereby.

CONSTITUTION: Pistons 3, 5 are movably arranged in cylinders 7, 9 sealing operation fluid therein and housed in a housing 1. An external combustion engine has regenerators 19, 25 arranged between an expansion chamber and a compression chamber determined by the piston 3, 5, and heat exchangers 21, 23, 27, 29. The regenerators 19, 25 are prepared by scatterning and connecting a plurality of mesh-like heat accumulation bodies to form ring-like or cylindrical sintered products. They are sintered products each having a specified shape by scatterning and connecting foamed metal, metal balls, metal fibers, metal short strips. Such regenerators 19, 25 are directly assembled in the housing. Low heat conductive ratio material such as thermosetting resin or ceramic is coated on an outer peripheral surface of the heat accumulation body of the regenerator and an inner wall surface of the housing in which the regenerators are assembled.

COPYRIGHT: (C)1995,JPO